



Safety Data Sheet

Page 1 of 10

LOCTITE EA 9492 A

SDS No. : 204340

V001.4

Revision: 03.05.2016

printing date: 28.12.2016

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name:

LOCTITE EA 9492 A

Other means of identification:

Loctite 9492A Kit component

Product code:

IDH926189

Recommended use of the chemical and restrictions on use

Intended use:

2-Component epoxy adhesive

Identification of manufacturer, importer or distributor

Manufacturer: Henkel S.p.A., Milano, Via C. Amoretti No. 78, 20157 Milano, Italy. Phone: +39-2-357-921 Fax: +39-2-355-2550

Importer: Henkel Thailand Ltd The Offices at Centralworld, 35th Floor, 999/9 Rama 1 Rd, Kwang Patumwan, Khet Patumwan, Bangkok 10330, Thailand. Phone : + 6622098000 Fax : +6622098008

E-mail address of person responsible for Safety Data Sheet:

ap-ua-psra.sea@henkel.com

Emergency information:

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

Hazard Class

Skin corrosion/irritation
Serious eye damage/eye irritation
Skin sensitizer
Chronic hazards to the aquatic environment

Hazard Category

Category 2
Category 2
Category 1
Category 2

GHS label elements:

Hazard pictogram:



Signal word:

Warning

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precaution:**Prevention:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Disposal:

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Section 3. Composition / information on ingredients**Substance or Mixture:**

Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	30- 60 %	Skin corrosion/irritation 2 H315 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	10- 30 %	Skin corrosion/irritation 2 H315 Serious eye damage/eye irritation 2A H319 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 2 H401 Chronic hazards to the aquatic environment 2 H411
Talc 14807-96-6	10- 30 %	
Titanium dioxide 13463-67-7	1- 10 %	

Section 4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

Indication of immediate medical attention and special treatment needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media:

Carbon dioxide, foam, powder

Specific hazards arising from the chemical:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice:

In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.
Wash spillage site thoroughly with soap and water or detergent solution.
Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling:

Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.
See advice in section 8

Storage:

Store in a cool, well-ventilated place.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

TALC, CONTAINING NO ASBESTOS FIBERS, RESPIRABLE FRACTION 14807-96-6	Value type	Time Weighted Average (TWA):
	mg/m³	2
	Remarks	ACGIH The value is for particulate matter containing no asbestos and <1% crystalline silica.
TALC - NON-ASBESTOS FORM 14807-96-6	Value type	Time Weighted Average (TWA):
	Remarks	TH OEL
TITANIUM DIOXIDE 13463-67-7	Value type	Time Weighted Average (TWA):
	mg/m³	10
	Remarks	ACGIH

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Body protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Engineering controls:

Ensure good ventilation/extraction.

Hygienic measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

Section 9. Physical and chemical properties**Appearance:**

grey, opaque
paste

Odor:

odourless

Odor threshold (CA):

No data available.

pH:	Not applicable
Melting point / freezing point:	No data available.
Specific gravity:	No data available.
Boiling point:	> 260.0 °C (> 500 °F)
Flash point:	> 248.0 °C (> 478.4 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure: (; 50 °C (122 °F))	< 0.0300000 mbar
Vapor density:	No data available.
Density:	1.5200 - 1.5600 g/cm ³
Solubility:	No data available.
Partition coefficient: n-octanol/water:	No data available.
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity: (Cone and plate; 25 °C (77 °F); Method: ; LCT STM 738; Rheological Data from flow curves)	10,000 - 20,000 mPa.s
VOC content: (2010/75/EC)	< 3.00 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials:

Reaction with strong acids.

Reacts with strong oxidants.

Chemical stability:

Stable under recommended storage conditions.

Conditions to avoid:

No decomposition if used according to specifications.

Hazardous decomposition products:

carbon oxides.

Section 11. Toxicological information

Symptoms of Overexposure: SKIN: Redness, inflammation.
SKIN: Rash, Urticaria.
EYE: Irritation, conjunctivitis.

Acute oral toxicity:

Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 9003-36-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	Not specified
Talc 14807-96-6	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rat
	Method	EU Method B.1 (Acute Toxicity (Oral))
Titanium dioxide 13463-67-7	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Acute inhalative toxicity:

Titanium dioxide 13463-67-7	Value type	LC50
	Value	> 6.82 mg/l
	Exposure time	4 h
	Species	rat
	Method	

Acute dermal toxicity:

Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 9003-36-5	Value type	LD50
	Value	> 2,000 mg/kg
	Species	rabbit
	Method	Not specified
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	Value type	LD50
	Value	23,000 mg/kg
	Species	rabbit
	Method	
Titanium dioxide 13463-67-7	Value type	LD50
	Value	≥ 10,000 mg/kg
	Species	hamster
	Method	

Skin corrosion/irritation:

Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 25068-38-6	Result	slightly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Talc 14807-96-6	Result	slightly irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	Result	not irritating
	Exposure time	4 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Titanium dioxide 13463-67-7	Result	NOAEL=1,000 mg/kg
	Route of application	oral: gavage
	Exposure time / Frequency of treatment	90 ddaily
	Species	rat
	Method	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

Ecotoxicity:

Toxic to aquatic life with long lasting effects., Do not empty into drains / surface water / ground water.

Toxicity:

Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	Value type	EC50
	Value	1.6 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	Value type	EC50
	Value	1.8 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	LC50
	Value	1.75 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss (reported as Salmo gairdneri)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Value type	EC50
	Value	9.4 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	2.4 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Scenedesmus capricornutum
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Talc 14807-96-6	Value type	LC50
	Value	> 100 g/l
	Acute Toxicity Study	Fish
	Exposure time	24 h
	Species	Brachydanio rerio (new name: Danio rerio)
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	Value type	LC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Fish
	Exposure time	48 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Titanium dioxide 13463-67-7	Value type	EC50
	Value	> 1,000 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	Value type	EC0
	Value	> 10,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	24 h
	Species	Pseudomonas fluorescens
	Method	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

Persistence and degradability:

Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 9003-36-5	Result	
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) 25068-38-6	Result	
	Route of application	aerobic
	Degradability	5 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

Section 13. Disposal considerations

Product

Method of disposal:

Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Section 14. Transport information

Road transport ADR:

Class: 9
Packing group: III
Classification code: M6
Hazard ident. number: 90
UN no.: 3082
Label: 9
Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)

Railroad transport RID:

Class: 9
Packing group: III
Classification code: M6
Hazard ident. number: 90
UN no.: 3082
Label: 9
Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)

Inland water transport ADN:

Class: 9
Packing group: III
Classification code: M6
Hazard ident. number: 90
UN no.: 3082
Label: 9
Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)

Marine transport IMDG:

Class:	9
Packing group:	III
UN no.:	3082
Label:	9
EmS:	F-A ,S-F
Seawater pollutant:	Marine pollutant
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)

Air transport IATA:

Class:	9
Packing group:	III
Packaging instructions (passenger):	964
Packaging instructions (cargo):	964
UN no.:	3082
Label:	9
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)

Section 15. Regulatory information

Regulatory Information:

Ministry of Industry Notice. The system to classify and communicate the hazard of hazardous material, BE. 2555

Global inventory status:

Regulatory list	Notification
TSCA	yes
DSL	yes
ENCS (JP)	yes
KECI (KR)	yes
PICCS (PH)	yes
IECSC	yes
NZIOC	yes

Section 16. Other information

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.