

PRODUCT INFORMATION



Lubricants - Engine Oil - Heavy Duty Engine Oils

Version: **106/08c**

Valvoline™ HD Engine Oil SAE 30

Quality single grade formulation for heavy-duty applications

Valvoline HD Engine Oil SAE 30 is a premium conventional, heavy-duty motor oil, for use in gasoline and diesel engines where the engine manufacturer recommends a single grade motor oil.

Performance levels

API: CF

Applications

Suitable for heavy-duty engines where single grade motor oils are recommended.

Specially engineered for use in service fleets where it helps prevent formation of sludge caused by frequent stop-and-go driving.

Can also be used, in some cases, as hydraulic oil or gear oil where specified by the manufacturer of the machine.

Can be used as hydraulic oil with the ISO 100 qualification.

Features & Benefits

Wear protection

Strong oil film protects the engine against wear and corrosion.

Engine cleanliness

Helps prevent formation of sludge caused by frequent stop-and-go driving.

Breakdown resistance

Thermal and Oxidation stable oil film.

Marine application

Suitable for use in older marine engines of pleasure boats.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

HD Engine Oil	
SAE Viscosity Grade	30
Viscosity, mm ² /s @ 100 °C. ASTM D-445	10,5
Viscosity, mm ² /s @ 40 °C. ASTM D-445	73
Viscosity Index ASTM D-2270	129
TBN, mg KOH/g ASTM D-2896	7,1
Pour Point, °C ASTM D-5949	-36
Specific Gravity @ 15.6°C. ASTM D-4052	0,871
Flash Point, COC, °C. ASTM D-92	242

**This information only applies to products manufactured in the following location(s):
Europe**

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 106/07c

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.